

CERTIFICATE of Compliance

U.S. ALLOY CO.

dba Washington Alloy 7010-G Reames Rd. Charlotte, NC 28216 www.weldingwire.com

Quality Management System in accordance with ISO 9001:2000 Cert # 05-R0925

TRADE NAME: USA 70S-3 Specification: AWS A 5.18 : ASME SFA 5.18

Classification: ER70S-3

Chemical Composition % for Weld Wire

1	AWS Requirements	Typical ¹
Carbon (C)	0.06-0.15	0.10
Manganese (Mn)	0.90-1.40	1.00
Silicon (Si)	0.45-0.75	0.55
Phosphorus (P)	0.025 max.	0.012
Sulfur (S)	0.035 max.	0.012
Nickel (Ni)	0.15 max.	
Molybdenum (Mo)	0.15 max.	
Copper (Cu)	0.50 max.	
Chromium (Cr)	0.15 max.	
Vanadium (V)	0.03 max.	

Mechanical Properties

	Minimum AWS Requirement	s Typical ¹
Tensile Strength	70,000 psi	75,500 psi
Yield Strength	58,000 psi	62,400 psi
Elongation in 2"	22 %	30.7%
Charpy V-notch Impact Average	20 ft · lbs at 0°F	66 ft lbs at 0°F

This certification is provided by Washington Alloy Co. with the expressed understanding that if the product supplied fails to conform the stated specifications, there shall be no personal liability of any kind on the undersigned and the obligation and liability of Washington Alloy Co., with respect to such non-conformance or specification failure, shall be limited to a) an obligation to furnish the purchaser, at no additional charge, material that meets the specifications and conformances or b) to refund to the purchaser the full amount of money paid to Washington Alloy Co. for the return of the product in full. In no event shall Washington Alloy Co. be liable for consequential damage.

This certifies that the product supplied will meet the requirements of the noted classification and data above. Products supplied in accordance to the Quality Management System of Washington Alloy Company.

Typical Results based on 100% CO₂

EAST COAST

7010-G Reames Rd

Tel (888) 522-8296

Fax (704)598-6673

Charlotte, NC 28216

GULF COAST
4855 Alpine Drive #190
8535 Utica Ave

Stafford, TX 77477 Rancho Cucamonga, CA 91730 Tel (877) 711-9274 Tel (800) 830-9033

Fax (281)313-6332 Fax (909)291-4586

Warehouse Distribution Center - Dayton, Ohio

Head Office – Puyallup, Washington

Print Date: 6/14/2008

Washington Alloy Company believes that all information and data given is correct. Use this information to assist in making your own evaluations or decisions and this information should not be mistaken as an expressed or implied warranty. U.S. ALLOY CO. assumes no liability for results or damages incurred from the use of any information contained herein, in whole or in part.