

Quality Management System in accordance with ISO 9001:2000 Cert # 05-R0925

CERTIFICATE of Compliance

TRADE NAME: USA 308L-16 Specification: AWS A 5.4 : ASME SFA 5.4

Classification: E308L-16



dba Washington Alloy 7010-G Reames Rd. Charlotte, NC 28216 www.weldingwire.com





Certification Administrator

Chemical Composition for Undiluted Weld Metal

	AWS Requirements	Typical
Carbon (C)	0.04 max.	0.03
Chromium (Cr)	18.00-21.00	19.58
Nickel (Ni)	9.00-11.00	10.20
Molybdenum (Mo)	0.75 max.	
Manganese (Mn)	0.5-2.5	1.03
Silicon (Si)	1.00 max.	0.40
Phosphorus (P)	0.04 max.	0.018
Sulfur (S)	0.03 max.	0.010
Copper (Cu)	0.75 max.	

Mechanical Properties	AWS Requirements min.	Typical
Tensile Strength	75,000 psi	80,000 psi
Yield Strength	Not required	55,000 psi
Charpy V-notch Impact Average	Not required	
Elongation in 2"	35 %	46 %
Ferrite Content	Not required	

This certification is provided by Washington Alloy Co. with the expressed understanding that if the product supplied fails to conform the stated specifications, there shall be no personal liability of any kind on the undersigned and the abligation and liability of Washington Alloy Co., with respect to such non-conformance or specification failure, shall be limited to a) an obligation to furnish the purchaser, at no additional charge, material that meets the specifications and conformances or b) to refund to the purchaser the full amount of money paid to Washington Alloy Co. for the return of the product in full. In no event shall Washington Alloy Co. be liable for consequential damage.

This certifies that the product supplied will meet the requirements of the noted classification and data above. Products supplied in accordance to the Quality Management System of Washington Alloy Company.

EAST COAST
7010-G Reames Rd

GULF COAST
4855 Alpine Drive #190

8535 Utica Ave

Charlotte, NC 28216 Stafford, TX 77477 Rancho Cucamonga, CA 91730 WA ALLOY Tel (888) 522-8296 Tel (877) 711-9274 Tel (800)830-9033

Fax (704)598-6673 Fax (281)313-6332 Fax (909)291-4586

Warehouse Distribution Center – Dayton, Ohio Head Office – Puyallup, Washington

Washington Alloy Company believes that all information and data given is correct. Use this information to assist in making your own evaluations or decisions and this information should not be mistaken as an expressed or implied warranty. U.S. ALLOY CO. assumes no liability for results or damages incurred from the use of any information contained herein, in whole or in part.