


Horizontal Fillet Weld on Steel Feet per pound of alloy

U.S. ALLOY CO. dba Washington Alloy 7010-G Reames Rd. Charlotte, NC 28216 www.weldingwire.com





Size of fillet "S"	Stick Electrodes	Cored Wire	Solid wire
1/8"	20.40816	29.41176	33.33333
3/16"	8.77193	12.65823	14.28571
1/4"	5.181347	7.518797	8.474576
5/16"	3.311258	4.807692	5.434783
3/8"	2.304147	3.355705	3.773585
1/2"	1.293661	1.883239	2.118644
5/8"	0.829876	1.206273	1.356852
3/4"	0.576037	0.837521	0.942507
1"	0.323939	0.471032	0.529101

Other Density Factors that may help (Feet divided by factor)

Deox Copper	1.14
Phos Bronze	1.13
Silicon Bronze	1.09
308, 309	1.01
316, 347	1.03
Titanium	0.75
1100 Aluminum	.346
4043 Aluminum	.343
5356 Aluminum	.339
Magnesium (AZ61A)	.231

These calculated averages are guidelines to help in estimating your approximate needs and cost the exact amount will depend on many factors

EAST COAST 7010-G Reames Rd Charlotte, NC 28216 Tel (888) 522-8296 Fax (704)598-6673 GULF COAST 4855 Alpine Drive #190 Stafford, TX 77477 Tel (877) 711-9274 Fax (281)313-6332 WEST COAST 5-2009 DC 8535 Utica Ave Rancho Cucamonga, CA 91730 Tel(800)830-9033 Fax (909)291-4586

Warehouse Distribution Center - Dayton, Ohio

Head Office – Puyallup, Washington

Washington Alloy Company believes that all information and data given is correct. Use this information to assist in making your own evaluations or decisions and this information should not be mistaken as an expressed or implied warranty. U.S. ALLOY CO. assumes no liability for results or damages incurred from the use of any information contained herein, in whole or in part.