

RMA ROSIN Liquid Flux

U.S. ALLOY CO. dba Washington Alloy 7010-G Reames Rd. Charlotte, NC 28216 www.weldingwire.com





Quality Management System in accordance with ISO 9001:2000 Cert # 05-R0925

This Rosin Mildly Activated rosin flux used in electronic soldering applications yielding excellent soldering activity. Common applications may include printed circuit boards, wire leads, cables and may other electronics applications. This light brown liquid consists of water-white rosin with brominated organic activators in a multi-component solvent. It is completely free of chlorides, free acidities, and inorganic cations. The residues are non-corrosive, non-conductive and fungus-free making it idea for items & parts where resides can not be removed.

PHYSICAL DATA:

Color Light Brown liquid with alchol smell

Soldering Range 340-500° F (175-390°C) Specific Gravity 0.86 @ 68° F (20° C)

Density 7.16 lbs/gallon @ 68° F (20° C) Residues Non-corrosive, Non-conductive

AVAILABLE SIZES:

TAFRMA-01 = 16 oz bottle

SPECIFICATIONS:

MIL-F-14256 Type RMA

This certifies that the product supplied will meet the requirements of the noted classification and data above. Products supplied in accordance to the Quality Management System of Washington Alloy Company.

EAST COAST
7010-G Reames Rd
Charlotte, NC 28216
Tel (888) 522-8296
Fax (704)598-6673
GULF COAST
4855 Alpine Drive #190
Stafford, TX 77477
Tel (877) 711-9274
Fax (281)313-6332

WEST COAST 8535 Utica Ave Rancho Cucamonga, CA 91 Tel(800)830-9033

Fax (909)291-4586

9-2007 DC

Warehouse Distribution Center - Dayton, Ohio

Head Office - Puyallup, Washington

Washington Alloy Company believes that all information and data given is correct. Use this information to assist in making your own evaluations or decisions and this information should not be mistaken as an expressed or implied warranty. U.S. ALLOY CO. assumes no liability for results or damages incurred from the use of any information contained herein, in whole or in part.